

JC20 Rec'd PCT/PTO 19 SEP 2005

Device for blocking and adjusting the inclination of
fittings

Description

5

The invention relates to a device for blocking and adjusting the inclination of fittings, in particular for adjusting the inclination with respect to each other of two components situated on a vehicle seat, such as a seat part and a backrest part, having a first fitting part which has a latching toothing, and a latching element which has a mating latching toothing, the latching toothing and the mating latching toothing being able to be brought into engagement and being able to be arrested in the engagement position by means of a clamping element which is under the force of a spring, acts on the latching element and is movable counter to the force of the spring via adjusting means.

20 Prior art

Devices of this type are disclosed in the documents DE 198 45 698 A1, DE 195 22 854 A1 and US 4 836 608 A. In the case of the device for blocking adjustment fittings on vehicle seats according to DE 198 45 698 A1, which adjustment fittings have a latching region which has a toothing, and a latching element which has a mating toothing, the toothing and the mating toothing can be brought into and out of engagement and can be arrested in the engagement position. The subject matter of the application relates to a special tooth design, according to which, in the engagement position, the tooth tips at their apex maintain a distance from the corresponding tooth roots of the respectively opposite elements and the corresponding toothings bear against one another by means of the tooth flanks. The tooth flanks are connected to the apex via a curved transition region

- 2 -

beginning at their tip end. The connection region, which is situated at the end of the tooth flanks, between tooth flanks and transition region is arranged displaced in the direction of the tooth root of the
5 opposite element by means of a reduction of the transition radius. This design is intended to provide greater safety in the event of a crash.

The fitting for adjusting the inclination of backrests
10 of motor vehicle seats that is disclosed in DE 195 22 854 A1 has a first articulated part and a second articulated part, one of which is connected fixedly to the seat and the other of which is connected fixedly to the backrest. In this case, the second
15 articulated part is coupled pivotably to the first articulated part and has a latching toothing which can be fixed in different pivoting positions by means of a locking lever formed for engagement therewith. The locking lever has a mating toothing corresponding to
20 the latching toothing of the second articulated part. The two toothings can be blocked in engagement divisions by means of a blocking lever. The blocking lever is mounted pivotably on the first articulated part, and locking lever and blocking lever have
25 mutually complementary control surfaces. The blocking lever in turn bears an arresting lever, which is mounted pivotably, can be displaced via an adjusting means and has a projection which, in a first pivoting position of the arresting lever and in the blocking
30 position of the blocking lever, bears against a stop surface of the first articulated part. In a second pivoting position, the projection is situated away from the stop surface of the first articulated part and therefore permits blocking lever and locking lever to
35 pivot so as to be free. Here, too, this design is intended to provide greater safety in the event of a crash, in particular a satisfactory blocking of the pivoting position which has been set.

The device according to US 4 836 608 A also has a similar construction to the abovementioned fittings. In all of the known devices, the clamping element, which
5 is also referred or could also be referred to as clamping cam, unit of blocking lever and arresting lever, "operation lever" or clamping eccentric, is driven via a tension spring which is fastened to this component and under the action of which the clamping
10 element is moved into or secured in a position which produces or secures the engagement position of the latching element.

As adjusting means in order to move the clamping
15 element counter to the force of the spring in such a manner that the latching element comes out of engagement, Bowden cables are mentioned and illustrated in DE 195 22 854 A1 and in DE 198 45 698, and a handling device designed integrally with the clamping
20 element is mentioned and illustrated in US 4 836 608 A. GB 2 059 496 A describes a device for blocking and adjusting the inclination of fittings, but which is not constructed according to the type described at the beginning, for which a transmission rod is used as
25 adjusting means. The transmission rod engages at both of its ends in fittings which are fitted on both sides of a seat.

The known use of tension springs for arresting and
30 producing the engagement position has an unfavorable effect on the designing of the construction space, the "package", due to the required length of the springs and may also cause noises during the actuation due to the friction occurring in their attachment means during
35 rotation. Since the spring is pivoted during the actuation, the spring may also, because of the changing angular position of the spring, have a force/travel characteristic in which the adjusting force, with

increasing distance of the latching element from the fitting part with the latching toothing in an end region, no longer - as desired - rises, but rather drops again after a dead center position is exceeded.

5 During a manual adjustment, this may undesirably influence the operator's sensation of control during actuation.

Object

10

The invention is based on the object of improving a device for blocking and adjusting the inclination of the type described at the beginning using structurally simple means such that a more favorable design of the construction space can be obtained, production of noise

15 can be damped and an improved sensation of control during actuation can be produced for the operator.

Achievement

20

This object is achieved by a device for blocking and adjusting the inclination of the type described at the beginning, in which the clamping element has a toothing in which a mating toothing situated on a toothed

25 element engages, the force of the spring acting on the toothed element and acting indirectly on the clamping element via the toothing and mating toothing.

In a preferred embodiment which is particular favorable

30 in terms of construction space, the spring can form a constructional unit with the toothed element, which comprises a toothed element which is designed in the manner of a toothed wheel and is driven by a leg spring or spiral spring, in particular flat spiral spring,

35 which is favorable in terms of construction space. Torsion springs of this type do not change their angular position when they become effective, and can advantageously also be dimensioned in such a manner

- 5 -

that they have a desired, for example a linearly or progressively rising, force/travel characteristic.

Further advantageous embodiments of the invention are
5 contained in the subclaims and the special description
below. The invention is explained in more detail with
reference to two exemplary embodiments illustrated in
the attached drawing.

10 In the drawing:

fig. 1 shows, in a cut open, perspective illustration,
a device according to the invention for
blocking and adjusting the inclination, in a
15 first embodiment,

fig. 2 shows, in an enlarged illustration in
comparison to fig. 1, a clamping element and a
constructional unit of toothed element and
20 spring of a device according to the invention
for blocking and adjusting the inclination,
according to the first embodiment of the
invention,

25 fig. 3 shows, in an enlarged illustration in
comparison to fig. 1, a clamping element and a
constructional unit of toothed element and
spring of a device according to the invention
for blocking and adjusting the inclination,
30 according to a second embodiment of the
invention,

fig. 4 shows, in a perspective illustration, a molded
part which can be used in an advantageous
35 development of the invention.

In the various figures of the drawing, identical parts
are always also provided with the same reference

numbers, with the result that they are generally also only described once in each case.

5 A device according to the invention for blocking and adjusting the inclination of fittings can be used in particular for adjusting the inclination with respect to each other of two components situated on a vehicle seat, such as a seat part and a backrest part.

10 As fig. 1 shows, a device of this type for blocking and adjusting the inclination comprises a first fitting part 1 which has a latching tothing 1a, and a latching element 2 which has a mating latching tothing 2a and is designed in the manner of a pivotable pawl. The
15 latching tothing 1a and the mating latching tothing 2a can be moved into engagement - and, if appropriate, as for the case illustrated in which this does not take place under the action of gravity, also out of engagement - and can be arrested in the engagement
20 position by means of a clamping element 3 which acts on the latching element 2 and can be moved via adjusting means.

25 The clamping element 3 has, for moving the latching element 2, a control contour 3a which is used for interacting with a corresponding control contour 2b of the latching element 2.

30 In order to securely hold the latching element 2 in its engagement position in the latching tothing 1a of the first fitting part 1, i.e. in the self-locking pivoting position illustrated in fig. 1, even in the event of dynamic loads, the clamping element 3 is spring-loaded. For this purpose, the clamping element 3 has a tothing
35 3b in which a mating tothing 4a situated on a toothed element 4 engages. In a manner favorable in terms of installation and construction space, the toothed element 4 forms with a spring 5 a constructional unit E

- 7 -

which can be arranged into an otherwise free construction space in the fitting part. The force of the spring 5 thereby acts indirectly on the clamping element 3 via the mating toothing 4a and toothing 3b.

5 In a preferred embodiment here, the spring 5 is designed as a torsion spring, to be precise as a leg spring, as fig. 2 also shows.

10 The toothing 3b of the clamping element 3 and the mating toothing 4a of the toothed element 4 are preferably designed as external toothings designed at least in the manner of segments, as illustrated in all of the figures. The first fitting part 1, the latching element 2, the clamping element 3 and the toothed element 4 can be pivoted relative to one another about
15 respective pivot axes X1, X2, X3, X4. In this case, if a bevel gear toothing is not used, the pivot axes X1, X2, X3, X4 are in particular arranged parallel to one another. The first fitting part 1, the latching element 2, the clamping element 3 and the toothed element 4
20 here have fastening openings O1, O2, O3, O4 which are arranged concentrically about their respective pivot axes X1, X2, X3, X4 and are partially filled, in particular in the case of the first fitting part 1 and the latching element 2, by corresponding fastening
25 elements (not referred to specifically).

The latching element 2, the clamping element 3 and the toothed element 4 are fastened to a second fitting part
30 6, the angular position of which, i.e. the inclination, relative to the first fitting part 1 can be changed and fixed with the aid of the device according to the invention for blocking and adjusting the inclination. The first fitting part 1 can be fastened, for example,
35 to a first component of a vehicle seat, such as a seat part, and the second fitting part 6 can be fastened to a second component of a vehicle seat, such as a backrest part, or vice versa.

As far as the construction of the second fitting part 6 is concerned, it should be noted that fig. 1 involves a cut open illustration of a device according to the invention. This means that the second fitting part is composed of the first wall 6a depicted and of a second wall (not illustrated) which covers the remaining components 1, 2, 3, 4, 5, is essentially identical in design and is connected fixedly to the first wall. The components 1, 2, 3, 4, 5 are held in or between these walls via the fastening elements which have already been mentioned, engage in the fastening openings O1, O2, O3, O4 and are not referred to specifically in the figures. The adjusting means (likewise not illustrated) for moving the clamping element 3 may preferably be at least one transmission rod which acts on the clamping element 3 and/or on the toothed element 4 and in particular engages axially in the respective fastening opening O3, O4 thereof.

The operation of the device according to the invention for blocking and adjusting the inclination is as follows:

In the illustration shown in fig. 1, there is a certain inclination with respect to each other of two components situated on a vehicle seat, such as a seat part and a backrest part. This inclination is expressed in the angular position of the first fitting part 1 with respect to the second fitting part 6. By means of the engagement of the latching tothing 1a of the first fitting part 1 in the mating latching tothing 2a of the latching element 2, this angular position is fixed and, by means of the clamping element 3 which is under the force of the spring 5, is secured. In order to bring the latching tothing 1a of the first fitting part 1 and the mating latching tothing 2a of the latching element 2 out of engagement, the toothed element 4 is moved counter to the force of the spring 5

with the aid of the adjusting means, to be precise is rotated in the direction of the arrow R4 shown in fig. 1. The engagement of the mating toothing 4a of the toothed element 4 in the toothing 3b of the clamping element 3 means that, in consequence, the clamping element 3 is rotated or pivoted in the direction of the arrow R3. Owing to the interaction of the, in particular lug-like, control contour 3a of the clamping element 3 with the corresponding control contour 2b of the latching element 2, which contour is designed in particular as an engagement opening, the latching element 2 is pivoted and, as a result, the engagement of the mating latching toothing 2a of the latching element 2 in the latching toothing 1a of the first fitting part 1 is canceled. The inclination of the first fitting part 1 relative to the second fitting part 6 can then be adjusted by pivoting about the axis X1. The adjusting force acting counter to the force of the spring 5 is then canceled, and the latching element 2 returns under the action of the spring 5 into its engagement division by dynamics proceeding inversely to the movements illustrated.

Fig. 2, which - as already mentioned - shows an enlarged detail from fig. 1, reveals that the toothed element 4 can advantageously be composed of an outer ring 4b and an inner ring 4c which are braced against each other by the spring 5. In this case, the spring 5 is arranged concentrically to the outer ring 4b and the inner ring 4c about the axis X4 and between the outer ring 4b and the inner ring 4c in a manner favorable in terms of construction space.

Fig. 3 shows a further advantageous design of the spring 5 in the constructional unit E formed from toothed element 4 and spring 5. The spring 5 here is designed as a spiral spring, in particular as a flat spiral spring, and is likewise arranged concentrically

- 10 -

about the axis X4 in the fastening opening O4 of the toothed element 4 in an extremely favorable manner in terms of construction space, i.e. in a space-saving manner. In this case, like the spring 5 in the first
5 embodiment, it is encircled by an outer ring 4b which bears the mating toothing 4a on its outer circumference.

Although the design according to figs. 1 and 2 is more
10 costly to manufacture in comparison with the embodiment according to fig. 3, it has the advantage, as a function of the seat geometry, that the transmission rod which can be fitted in the fastening opening O4 is arranged to the rear and therefore outside the comfort
15 region of the seat. If the seat geometry permits this, then for cost reasons the embodiment according to fig. 3 is preferably used.

The invention is not restricted to the exemplary
20 embodiments illustrated but rather also comprises all embodiments acting in an identical manner within the meaning of the invention. Thus, in particular, shaping, dimensioning and position of the constructional unit E and of its components toothed element 4 and spring 5
25 may differ from the embodiments illustrated. As an alternative to the fastening rods mentioned as being preferred, it is also possible for other means, such as, for example, the Bowden cables already mentioned, to be used as the adjusting means.

30 Furthermore, the expert can supplement the invention by means of additional advantageous measures without departing from the scope of the invention. Thus - as likewise illustrated graphically - a respective fine
35 toothing F3, F4 can be provided around the periphery of the fastening openings O3, O4 of clamping element 3 and/or toothed element 4, into which fine toothing a molded profile part 7 (fig. 4) for receiving one end of

- 11 -

a transmission rod, which is used as an adjusting means in order to bring the first fitting part 1 and the latching element 2 out of engagement, can be pressed coaxially (X2 and/or X3 with X7). In this case, the

5 bushing-like molded profile part 7 can have, in its fastening opening O7, a profiled inner contour K7 which can be positioned during the pressing-in operation in such a manner that the molded profile part 7 is arranged in a defined position with respect to the

10 second fitting part 6. This defined position may exist, for example, by the distance of a marking point of the inner contour K7 from one or more reference points of the second fitting part 6, such as the penetration points of the axes X2, X3 of the latching element 2 or

15 the clamping element 3. The effect achieved by this is that two devices according to the invention which are to be fitted on both sides of a seat part can be synchronized at a very early point, i.e. during the installation, and do not have to be coordinated with

20 each other in a higher stage of assembly. As a result, different positions of the clamping element 2 that occur due to tolerances are compensated for, and the transmission rod can be fitted in a manner free from distortion. The molded profile part 7 may take up any

25 desired position in an infinitely variable manner irrespective of the division of the inner contour K7, for example of a toothing of clamping element 3 and/or latching element 4.

Reference numbers

- 1 First fitting part
- 1a Latching tothing of 1
- 5 2 Latching element
- 2a Mating latching tothing of 2 to 1a
- 2b Control contour of 2
- 3 Clamping element
- 3a Control contour of 3, corresponding to 2b
- 10 3b Tothing of 3
- 4 Toothed element
- 4a Mating tothing of 2 to 3b
- 4b Outer ring of 4
- 4c Inner ring of 4
- 15 5 Spring
- 6 Second fitting part
- 6a Wall of 6
- 7 Molded profile part
- E Construction unit of 4 and 5
- 20 F3 Fine tothing in O3
- F4 Fine tothing in O4
- K7 Contour (tothing) in O7
- O1 Fastening opening of 1
- O2 Fastening opening of 2
- 25 O3 Fastening opening of 3
- O4 Fastening opening of 4
- O7 Fastening opening of 7
- R2 Directional arrow pivoting/rotational movement of 2
- 30 R3 Directional arrow pivoting/rotational movement of 3
- R4 Directional arrow pivoting/rotational movement of 4
- X1 Pivot axis of 1
- 35 X2 Pivot axis of 2
- X3 Pivot axis of 3
- X4 Pivot axis of 4